#### Permatex. Inc. 10 Columbus Blvd. Hartford, CT 06106 USA **Telephone: 1-87-Permatex** (877) 376-2839 Emergency: 800-255-3924 International Emergency: 813-248-0585

# **Material Safety Data Sheet**

### **1. PRODUCT IDENTIFICATION**

**Product Name:** Item No: **Product Type:** 

09179

COUNTERMANS CHOICE HI STR THREADLOCKER RED 1ML Anaerobic

2. COMPOSITION/INFORMATION ON INGREDIENTS				
Ingredient	Weight Percent	ACGIH TLV:	OSHA PEL:	
POLYGLYCOL DIMETHACRYLATE 25852-47-5	60-75	Not Listed	Not Listed	
POLYESTER RESIN 39382-25-7	20-30	Not Listed	Not Listed	
SACCHARIN 81-07-2	<5	10mg/m <sup>3</sup> nuisance dust	Not Listed	
N,N-DIALKYTOLUIDINE 613-48-9	<3	Not Listed	Not Listed	
DIMETHYLBENZYL HYDROPEROXIDE 80-15-9	<3	Not Listed	Not Listed	
METHANOL 67-56-1	0.1-1.0	200 ppm TWA	200 ppm TWA; 260 mg/m <sup>3</sup> TWA	

# 3. HAZARDS IDENTIFICATION

**Toxicity:** 

**Primary Routes of Entry:** 

May cause eye, skin and respiratory irritation. Methanol may cause blindness or death if swallowed. Eye and skin contact, ingestion, inhalation

Signs and Symptoms of Exposure:

Repeated skin contact may cause allergic skin reactions.

Ingredient	Weight Percent	NTP	ACGIH Carcinogens	IARC
SACCHARIN 81-07-2	<5	Delisted April 2000		Group 3: Vol 73, Page 517: 1999

**Medical Conditions Recognized as** Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product. Being Aggravated by Exposure:

#### FIRST AID MEASURES <u>4.</u>

Ingestion: Inhalation: **Skin Contact:** Eye Contact:

If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention. Move to fresh air in case of accidental inhalation of vapours. Wash off with soap and water. If skin irritation persists, call a physician. In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

# 5. FIRE FIGHTING MEASURES

Flash Point (°F/C): **Recommended Extinguishing Media: Special Fire-Fighting Procedures:** Hazardous Products of Combustion: **Unusual Fire/Explosion Hazards:** 

Lower Explosive Limit: **Upper Explosive Limit:** 

>200° F TOC Carbon Dioxide, Dry Chemicals, Foam. Firefighters should wear self-contained breathing apparatus. Irritating vapors None.

Not determined Not determined

#### 6. ACCIDENTAL RELEASE MEASURES Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until

**Spill Procedures:** 

# 7. HANDLING AND STORAGE

Storage: Store below 100 degrees F. Handling: Avoid prolonged skin contact. Keep away from eyes.

disposal.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	Safety glasses
Skin:	Rubber or plastic gloves.
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection:	An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Red liquid		
Odor:	MILD		
Boiling Point:	>400°F @ 760 mm		
pH:	Does not apply		
Solubility in Water:	Insoluble		
Specific Gravity:	1.1		
VOC Content(Wt.%):	2.5% by weight; 28 g/l		
Vapor Pressure:	<5 mm Hg		
Vapor Density (Air=1):	1.01		
Evaporation Rate:	Low		

## **10. STABILITY AND REACTIVITY**

**Chemical Stability:** Hazardous Polymerization: Incompatabilities: **Conditions to Avoid:** Hazardous Products of Combustion: Stable at normal conditions MAY OCCUR. Reducing agents Heat Irritating vapors

### 11. TOXICOLOGICAL INFORMATION

See Section 3

### 12. ECOLOGICAL INFORMATION

No data available

#### **13. DISPOSAL CONSIDERATIONS**

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations. **US EPA Waste Number:** NH - Not a RCRA Hazardous Waste Material

### **14. TRANSPORTATION INFORMATION**

DOT (49CFR 172)

Domestic Ground Transport	
DOT Shipping Name:	Unrestricted
Hazard Class:	None

Hazard Class:	None
UN/ID Number:	None
Marine Pollutant:	None

#### ΙΑΤΑ

Proper Shipping Name:	Not regulated
Class or Division:	None
UN/NA Number:	None

#### IMDG

Proper Shipping:	Unrestricted
Hazard Class:	None
UN Number:	None

### **15. REGULATORY INFORMATION**

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

DIMETHYLBENZYL HYDROPEROXIDE

#### CALIFORNIA PROP 65:

No California Prop 65 chemicals are known to be present.

TSCA Inventory Status: Listed on Inventory: YES All components of this product are listed (or exempt) on the EPA TSCA inventory.

### **16. OTHER INFORMATION**

Estimated NFPA Rating:HEALTH 1, FLAMMABILITY 1, INSTABILITY 1Estimated HMIS Classification:HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0NFPA is a registered trademark of the National Fire Protection Assn.HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:	Denise Boyd, Health and Safety Manager			<b>Revision Date</b>	: January/11/2007	
Company:	Permatex. Inc.	10 Columbus Blvd.	Hartford, C	T USA 06106	Revision Number:	2
					Number:	