Supplier: Permatex, Inc. 10 Columbus Blvd. Hartford, CT 06106 Telephone: 1-87-Permatex (877) 376-2839

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: Item No: Product Type: 137DA MOTOR MUSCLE CARB & CHOKE CLEANER 12OZ AE 80079 Aerosol cleaner

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Percent	ACGIH 8 Hr. TWA:	OSHA 8 Hr. TWA:
ACETONE 67-64-1	50-60	500 ppm TWA; 1188 mg/m3 TWA	1000 ppm TWA; 2400 mg/m3 TWA
TOLUENE 108-88-3	10-20	50 ppm TWA; 188 mg/m3 TWA	200 ppm TWA; C 300 ppm
PROPANE 74-98-6	10-20	simple asphyxiant; 2500 ppm TWA	1000 ppm TWA; 1800 mg/m3 TWA
XYLENE, MIXTURE OF ISOMERS 1330-20-7	10-20	100 ppm TWA; 434 mg/m3 TWA	100 ppm TWA; 435 mg/m3 TWA
ETHYL BENZENE 100-41-4	1-10	100 ppm TWA; 434 mg/m3 TWA	100 ppm TWA; 435 mg/m3 TWA

3. HAZARDS IDENTIFICATION

Toxicity:

Aspiration hazard if swallowed. Deliberately concentrating and inhaling the vapor may be harmful or fatal. Exposure to vapors or mist may result in irritation of the respiratory tract. Long term exposure to high concentrations of vapor may cause lung, liver or kidney damage. May cause eye and skin irritation. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage (sometimes referred to as "solvent" or "painter's syndrome"). Symptoms include fatigue, concentration difficulties, anxiety, depression, rapid mood swings, and short-term memory loss.

Primary Routes of Entry: Signs and Symptoms of Exposure: Eye and skin contact, ingestion, inhalation. Excessive overexposure may cause giddiness, dizziness, headache, nausea and in extreme cases, unconsciousness and respiratory depression. May cause redness to eyes and irritation to nasal passages.

Ingredients	Percent	NTP:	ACGIH Carcinogens	IARC:
ACETONE 67-64-1	50-60		A4 - Not Classifiable as a Human Carcinogen	
TOLUENE 108-88-3	10-20	male rat-no evidence; female rat-no evidence	A4 - Not Classifiable as a Human Carcinogen	
XYLENE, MIXTURE OF ISOMERS 1330-20-7	10-20	male rat-no evidence; female rat-no evidence; male mice-no evidence; female mice-no evidence	A4 - Not Classifiable as a Human Carcinogen	Group 3: Vol. 71, pg 1189, 1999
ETHYL BENZENE 100-41-4	1-10			Group 2: Vol. 77, pg 227, 2000

Medical Conditions Recognized as Being Aggravated by Exposure: Heart disease, respiratory disorders, liver and kidney diseases, amenia, rhythm disorders of the heart. Preexisting eye, skin and respiratory disorders may be aggravated by overexposure to this product.

4. FIRST AID MEASURES

Product Name:137DA MOTOR MUSCLE CARB & CHOKE CLEANER 120Z AEItem No:80079

Ingestion:	If swallowed, do NOT induce vomiting. Give victim two glasses of water, Call a physician immediately. Never give anything by mouth to an unconscious person.
Inhalation:	If inhaled, remove to fresh air. If not breathing give artificial respiration, preferably mouth-to-mouth. If breathing is difficult give oxygen. Get medical attention.
Skin Contact:	Remove contaminated clothing. Wash area with soap and water. If irritation persists, seek medical attention.
Eye Contact:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point (°F/C):	
Recommended Extinguishing Media:	Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures:	Firefighters should wear self-contained breathing apparatus. Keep containers cool. Use equipment or shielding required to protect against bursting or venting of containers. Water spray may be ineffective on flames but should be used to keep fire-exposed containers cool.
Hazardous Products Formed by Fire or	Oxides of carbon. Irritating vapors.
Thermal Decomposition:	
Unusual Fire/Explosion Hazards:	Contents under pressure. Exposure to temperatures over 120 degrees F. may cause bursting or venting. Use equipment or shielding to protect personnel from bursting containers.
Lower Explosive Limit:	1.0
Upper Explosive Limit:	12.8

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures:

Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal.

7. HANDLING AND STORAGE

Storage:

Store away from heat, sparks or open flame. Do not store at temperatures above 120 degrees F.
Exposure to high temperatures may cause container to burst.
Avoid contact with skin and eyes. Do not inhale vapors. Do not puncture or incinerate container. Do not use near heat, sparks or open flame. Extinguish all flames, pilot lights and heaters. Turn off stoves, electric tools and appliances, and other sources of ignition. Intentionally concentrating and inhaling the vapor may be harmful or fatal. Use only in a well ventilated area. Vapors may accumulate readily and may ignite explosively. Wash hands before eating, drinking, chewing gum, using tobacco

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes:	Safety glasses with side shields.
Skin:	Not normally required when using an aerosol. Wear chemical resistant gloves if repeated skin contact
	occurs or causes irritation.
Ventilation:	General; local exhaust ventilation as necessary to control any air contaminants to within their
	exposure limits during the use of this product.
Respiratory Protection:	An approved respirator (i.e. NIOSH, etc.) should be worn when exposures are expected to exceed the applicable limits.
Respiratory Protection:	

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Odor: Boiling Point (°F): pH: Solubility in Water: Specific Gravity: VOC Content(Wt.%): Vapor Pressure: Vapor Density (Air=1): Evaporation Rate: Clear liquid SOLVENT ODOR <0 to 292 degrees F. Does not apply Nil 0.75 45% by weight Not determined Heavier than air Faster than ether

or using the toilet.

10. STABILITY AND REACTIVITY

Chemical Stability: Hazardous Polymerization: Incompatabilities: Stable at normal conditions WILL NOT OCCUR Strong oxidizers.

Handling:

Product Name:137DA MOTOR MUSCLE CARB & CHOKE CLEANER 120Z AEItem No:80079

Conditions to Avoid: Hazardous Products Formed by Fire or Thermal Decomposition: Do not expose to heat or store at temperatures above 120 F. Oxides of carbon. Irritating vapors.

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal:

Disposal should be made in accordance with federal, state and local regulations. This container may be recycled in aerosol recycling centers. Before offering for recycling, empty the can by using the product according to the label. If recycling is not available, wrap the container and discard in the trash.

US EPA Waste Number:

D001 as per 40CFR 261.21

14. TRANSPORT INFORMATION

DOT (49CFR 172)	
Domestic Ground Transport	
DOT Shipping Name:	CONSUMER COMMODITY
Hazard Class:	ORM-D
UN/ID Number:	None
Marine Pollutant:	None
IATA	
Proper Shipping Name:	Consumer Commodity
Class or Division:	Class 9
UN/NA Number:	ID 8000
IMDG	
Proper Shipping:	Aerosols, Limited Quantity
Hazard Class:	Class 2.1
UN Number:	UN 1950

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical. XYLENE, ETHYL BENZENE, TOLUENE

CALIFORNIA PROP 65:

WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA Inventory Status:

All components of this product are listed (or exempt) on the EPA TSCA inventory.

16. OTHER INFORMATION

Estimated NFPA Rating:	HEALTH 2, FLAMMABILITY 4, REACTIVITY 0		
Estimated HMIS Classification:	HEALTH 2, FLAMMABILITY 4, PHYSICAL HAZARD 0		

NFPA is a registered trademark of the National Fire Protection Assn. HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By:	Denise Boyd	Health and Safety Manager		
Company:	Permatex. Inc.	10 Columbus Blvd.	Hartford, CT	06106
Telephone Number:	1-87-Permatex	(877) 376-2839		

Revision Date: 06/19/2002

Revision Number: 0