



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT & COMPANY IDENTIFICATION

Product name	CC-2000 Color Series
Product name(s) covered	See Section 16 for Product Names Covered.
MSDS name	CC-2000 Color Series
CAS number	Mixture
Generic description	Sealant
Manufacturer	Bostik, Inc. 211 Boston Street Middleton, MA 01949 USA
24 hour emergency assistance	Telephone: 1-800-227-0332
General assistance	Telephone: 1-978-777-0100
MSDS assistance	Telephone: 1-414-607-1347

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component(s)	CAS #	Percent
Methyl alcohol	67-56-1	< 1.5
Composition comments	Methyl alcohol can be formed through hydrolysis and be released during the curing process.	

3. HAZARDS IDENTIFICATION

Emergency overview	Harmful: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. Methyl alcohol is formed during curing. Provide ventilation adequate to control vapor exposure within inhalation guidelines when handling.
Potential health effects	
Skin	Skin contact may cause irritation.
Eyes	This product may cause irritation to the eyes.
Inhalation	This product may cause irritation to the respiratory system. Methyl alcohol is formed during curing. Use with adequate ventilation. Repeated inhalation may be harmful; lung irritation and serious central nervous system disorders may result. Inhalation of vapours in high concentration can cause narcotic effects and metabolic acidosis.
Ingestion	This product can cause gastrointestinal irritation, nausea, vomiting, and diarrhea. Ingestion of this product may result in central nervous system effects including headache, sleepiness, dizziness, slurred speech and blurred vision. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.
Target organs	Central Nervous System. Kidneys and Liver.
Signs and symptoms of overexposure	Inhalation of Methyl alcohol vapors in high concentrations may cause nausea, abdominal pain, vomiting, headache, dizziness, shortness of breathe, weakness, fatigue, leg cramps, restlessness, confusion, drunken behavior, visual disturbances, drowsiness, coma, and death. Visual effects may include blurred vision, diplopia, changes in color perception, restriction of visual fields, and complete blindness. Ingestion of moderate quantities of Methyl alcohol produces metabolic acidosis. Onset of symptoms may be delayed up to 48 hours. OSHA has established a PEL of 200 ppm, 8 hour TWA. Provide ventilation adequate to control vapor exposure within inhalation guidelines when handling.

4. FIRST AID MEASURES

First aid	
Skin	Remove contaminated clothing to prevent further skin exposure and dispose of properly. In situations involving considerable skin contact, place the contaminated person in a deluge shower for at least 15 minutes. For minor exposures, wash thoroughly with soap and clean water. Get medical attention if irritation persists.
Eye	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	Remove to fresh air. Get medical attention immediately for a large dose exposure or if cough or other symptoms develop.

Ingestion	If ingested, get immediate medical attention. Do not induce vomiting unless instructed to do so by medical personnel. Never give anything by mouth to a victim who is unconscious or is having convulsions.
Notes to physician	Treat symptomatically and supportively. Contact Bostik to determine whether any additional information is available. If overexposure to the solvents in this product is suspected, testing should include nervous system and brain effects including recent memory, mood, concentration, headaches and altered sleep patterns. Liver and kidney function should be evaluated. This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

5. FIRE FIGHTING MEASURES

Extinguishing media	Use dry chemical, carbon dioxide, or foam. Water spray (fog).
Dust explosion hazard	None Known
Sensitivity to mechanical impact	None Known
Sensitivity to static discharge	None Known
Fire fighting equipment/instructions	Firefighters should wear full protective clothing including self contained breathing apparatus.
Flash point	285 °F (140.6 °C)

6. ACCIDENTAL RELEASE MEASURES

Emergency action	Appropriate safety measures and protective equipment should be used. See Section 8. Do not discharge to lakes, streams, ponds, or sewers. Dispose of in compliance with local, state, and federal regulations.
Spill or leak procedure	Scrape up paste and place in steel drums that are in good condition. Thoroughly clean area where spill occurred.
Reporting	See Federal reporting requirements listed in Section 15. We recommend you contact local authorities to determine if there may be other local reporting requirements.

7. HANDLING & STORAGE

Handling	Wash hands thoroughly after handling, especially before eating, drinking, smoking, and using restroom facilities. Wash contaminated goggles, face shields, and gloves. Professionally launder contaminated clothing before re-use.
Storage	Store in a cool, dry, well-ventilated area away from heat, ignition sources and direct sunlight. Water contamination should be avoided. Cool location should be 60-80 degrees F or 15-30 degrees C.
Empty container precaution	Attention! Follow label warnings even after container is emptied since empty containers may retain product residues. Do not reuse empty container without professional cleaning for food, clothing, or products for human or animal consumption, or where skin contact can occur.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls	Use local exhaust or general ventilation where the potential exists to exceed the PEL or TLV exposure limits. Methyl alcohol is formed during curing. Methyl alcohol vapors are toxic and flammable so special ventilation may be needed.
Eye protection	Wear goggles or safety glasses with side shields.
Skin and body protection	Wear appropriate clothing to minimize skin contact with this product.
Respiratory protection	If ventilation is not sufficient to effectively prevent buildup of vapors, appropriate NIOSH/MSHA respiratory protection must be provided

Exposure limits

ACGIH - Threshold Limits Values - Time Weighted Averages (TLV-TWA)

Methyl alcohol 67-56-1 200 ppm TWA

NIOSH - Pocket Guide - TWAs

Methyl alcohol 67-56-1 200 ppm TWA; 260 mg/m3 TWA

OSHA - Final PELs - Time Weighted Averages (TWAs)

Methyl alcohol 67-56-1 200 ppm TWA; 260 mg/m3 TWA

OSHA - Vacated PELs - TWAs

Methyl alcohol 67-56-1 200 ppm TWA; 260 mg/m3 TWA

9. PHYSICAL & CHEMICAL PROPERTIES

Target solids	100 %
Density	1.487 g/cc
Odor	Mild
Color	Various
Physical state	Paste
Freeze protect	No
VOC (Volatile Organic Compounds)	< 30 g/l

10. STABILITY & REACTIVITY

Hazardous reactions/decomposition products	Unknown due to the complex nature of this material. Fumes from complete or incomplete combustion may include carbon dioxide, carbon monoxide, water vapor, oxides of nitrogen and a wide variety of innocuous or toxic fumes.
Hazardous polymerization	Will not occur.
Conditions to avoid	Avoid Strong Acids.
Stability	This is a stable material.

11. TOXICOLOGICAL INFORMATION

Toxicological data If any toxicological data is available, it will be listed below:
LD50

Toxicology Data - Selected LD50s and LC50s

Methyl alcohol

67-56-1 Inhalation LC50 Rat: 83.2 mg/L/4H; Inhalation LC50 Rat: 64000 ppm/4H; Oral LD50 Rat: 5628 mg/kg; Dermal LD50 Rabbit: 15800 mg/kg

Carcinogenicity If this product contains any carcinogens, they will be noted below:

12. ECOLOGICAL INFORMATION

Ecotoxicological information No data available for this product.

13. DISPOSAL CONSIDERATIONS

It is the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable local, state and federal regulations.

Waste disposal Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

14. TRANSPORT INFORMATION

Department of Transportation (DOT) Requirements

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

15. REGULATORY INFORMATION

This MSDS is prepared and distributed pursuant to the Federal Hazard Communication Standard, 29 CFR 1910.1200.

Federal regulations All components are on the U.S. EPA TSCA Inventory List.

CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Methyl alcohol

67-56-1 5000 lb final RQ; 2270 kg final RQ

CERCLA/SARA - Section 313 - Emission Reporting

Methyl alcohol

67-56-1 1.0 % de minimis concentration

State regulations If this product contains any ingredients listed under California Proposition 65, they will be noted below:

International regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and contains all the information required by the Controlled Products Regulations.

All components are included on the Canadian Domestic Substances List (DSL).

HMIS Ratings Health: 2*
Flammability: 1
Physical hazard: 0
Personal protection: X

SARA 311/312 HAZARD CATEGORIES Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

WHMIS status Controlled

WHMIS labeling



WHMIS classification D2B - Other Toxic Effects-TOXIC

16. OTHER INFORMATION

Product name(s) covered A60400 - CC-2000 WHITE
A60412 - CC-2000 WHITE 24/10.1
A60414 - CC-2000 WHITE S/PK 12/20.0
A60911 - CC-2000 STONE 24/10.1
A60921 - CC-2000 STONE S/PK 12/20.0
A61610 - CC-2000 ALMOND 24/10.1
A61621 - CC-2000 ALMOND S/PK 12/20.0
A61710 - CC-2000 BRONZE 24/10.1
A61721 - CC-2000 BRONZE S/PK 12/20.0

Disclaimer The data in this MSDS has been compiled from publicly available sources. This data relates only to the designated product and not to the use of said product in combination with other materials. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards which exist. Responsibility for proper precautions and safe use of the product lies with the user. All data in this MSDS is typical of the product as a whole, and does not represent any individual lot or batch, therefore, Bostik, Inc. makes no warranty about the accuracy of the data herein and assumes no liability for the use of such data. It is the responsibility of the user to comply with all applicable federal, state, and local laws and regulations.

Further information Any characters following an individual item number are just designations for the various types of packaging that are available for this product. For example, a product "G12345-XX" is item number "G12345" with a packaging designation of "XX". These characters do not indicate a different product nor a different regulatory, health, safety and/or environmental status. This document covers the item numbers listed above for all of their packaging types.

Issue date 24-MAY-07

Prepared by Pam Larsen

Supersedes 22-NOV-06

MSDS sections updated Disposal Considerations: Waste Disposal
Other Information: Further Information